

CPE HOST CLUB EQUIPMENT LIST – Effective February 1, 2022

This form must be sent to each judge and course reviewer. One form must be submitted for each ring.

HOST CLUB: Canine Agility Training Society		TRIAL DATES: September 14-15, 2024	
RING DIMENSIONS: 100 by 100		A CRCD grid is required to be sent to each judge for that trial, and the judge's course reviewer.	
Any additional details to know for judging? Monadnock Humane Society outside ring has 2 entrance/exit gates.			
OBSTACLE	SPECIFICATIONS	DESCRIPTION	AVAILABLE Yes or No
<u>A-FRAME</u> <u>9'</u>	Constructed of wood, fiberglass or composite board and preferred surface is Wet-Apply Skin rubber granules. Also may be aluminum with Wet Apply Skin Rubber granules. Sprinkle-on rubber granules allowed. Slats are optional.	9' Rubber Granule wet apply method - Slats	No
		9' Rubber Granule wet apply method – Slatless	No
		9' Sprinkle Rubber Granule - Slats	Yes
		9' Sprinkle Rubber Granule - Slatless	No
	Can open tunnel fit lengthwise under A-frame?		Yes
<u>8' or 12'</u> <u>DOG WALK</u>	Is there a 12' dog walk available for this trial?	Slats or Slatless?	Slats
	Is there an 8' dog walk available for this trial?	Slats or Slatless?	No
	Constructed as above – slats are optional. Indicate at right description of surface. See rulebook for detailed requirements.	Rubber Granules Wet Apply Method	No
		Sprinkle on Rubber Granules	Yes
	Can open tunnel fit under center of dog walk as a half-circle?		Yes
	If “no” to above, can one side of tunnel fit under center?		
	Can one side of open tunnel fit under end plank of dog walk?		Yes
<u>TEETER</u>	Teeter will be 12' long, 12" wide plank with surface of wood fiberglass or composite board. Preferred surface is Wet Apply Skin rubber granules. Aluminum is allowed with Wet-Apply skin surface. Slats are optional.	Rubber Granules - slats	No
		Rubber Granules-slatless	Yes
<u>WALL JUMP</u>	Should have displaceable units on the top. Width of jumping area should be no less than 48", maximum of 65". Must include all CPE jump heights.		No
<u>TIRE JUMP</u>	Saloon door style. 24" aperture with 1" +/- tolerance. Must include all CPE jump heights.		No
<u>TABLE</u>	Must be adjustable to 4", 8", and 16" heights Rubber Granules required. See rulebook for rubber	Rubber Granules	Yes

OBSTACLE	SPECIFICATIONS	DESCRIPTION	Number Available
<u>OPEN TUNNELS</u>	Tunnels must be flexible with 24" openings (with allowance of 2") and 10' to 20' in length when extended. Must be opaque (black or clear tunnels are not acceptable)	10' to 12" long	
		15' long	3
		20' long	1
		3m long	
		5m long	
<u>BROAD JUMP</u>	There are four 8" planks, or five 6" planks, 4' to 5' long. Freestanding corner marker flags at least 1" wide and 36" high are recommended.	Hogback (Bi-directional)	
		One-way direction only	1
<u>SINGLE JUMPS</u>	Heights: 4", 8", 12", 16", 20", 24" measure from ground to top of pole – must have 4" cups Jump bars: 4' to 5' long, stripped with contrasting color(s). 1" PVC or square lightweight wood 1" to 2" square Uprights: Minimum 32" tall, at least 1" diameter (1.5 or more recommended) Wings to be 30" to 48" wide Poles are displaceable in either direction.	Wingless jumps	12
		Winged jumps (indicate wing width)	10
		5' jump bars	40
		4' or other size jump bars	
<u>ASCENDING DOUBLE JUMP</u>	Heights for first bar: Ground, 4", 8", 12", 16", 20" measure: ground to top of pole Heights for second bar: 4", 8", 12", 16", 20", 24" Bar spacing is 1/2 the height of second bar (center to center. 5' jump bars preferred.	Wingless Double Jumps	1
		Winged jumps (indicate wing width)	
<u>TRIPLE JUMP</u>	Heights for first bar: ground, 4", 6", 8", 10", 12"; second bar: ground, 6", 9", 12", 15", 18", third bar: 4", 8", 12", 16", 20", 24" Bar spacing: 2", 4", 6", 8", 10", 12" Jump bars must be 5' long	Wingless Triple Jump	1
		Winged Triple Jump (indicate wing width)	
<u>PANEL JUMP</u>	Heights are 4", 8", 12", 16", 20", 24" Panels consist of up to 6 planks, 4' to 5' long, 3" to 4" wide and up to 1" thick, resembling a solid wall, and displaceable in both directions.	Wingless Panel Jump	1
		Winged Panel Jump (indicate wing width)	
<u>WEAVE POLES</u> (base mounted)	Weave poles shall be 1" PVC, 36" to 48" tall, spaced 24" (center to center) with variance of no more than 1/2". Base is no more than 1/2" in height, and will be 2" to 4" wide. Stick-In-The-Ground weave poles may ONLY be used as an emergency substitution of equipment at an outdoor	3 poles per section	
		4 poles per section	
		5 poles per section	
		6 poles per section	4

MEASURING and TIMING DEVICES	AVAILABLE? Yes or No
Measuring Device (actual measurements)	No
Wickets - measurements of 8", 12", 16", 20", 24" to bottom of top cross bar Each wicket is marked for the respective P-card height, e.g. "P-4", "P-8",	Yes (CATS)
Is there a measuring wheel available for the judge?	Yes (CATS)
Will electronic timers be used?	Yes (CATS)
Will stopwatches be used? (Must have available as emergency back-up for E-timers)	No